

**SURFACE MOUNTED, 250/300 M INDUSTRIAL ROLLS
STAINLESS STEEL AISI 304 BRIGHT FINISH**

Code: PR0783C

General Description

- Toilet paper dispenser for industrial rolls of 250/300 m, surface mounted, stainless steel AISI 304 bright finish
- Manual dispensing.
- Robust and vandal-proof.
- Suitable for very high traffic facilities.
- Model suitable for public use.
- It generally goes along with a toilet brush and waste receptacle, stainless steel AISI 304 bright finish, complemented by a warm air hand dryer.

Components & Materials

- Stainless steel AISI 304 one-piece body, 0,8 mm thick, round Ø 250 mm, fully sealed and with a catch system to prevent the opening of the door, bright finish. The supports of the screws in the back of the appliance, are acting as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It is mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It includes a lock system with standard mediclinics® key, that allows opening the lid for replenishment.
- Stainless steel AISI 304 axis, 0,8 mm thick, for standard 45 mm paper roll tube, with inertial anti-spin retainer. The axis allows the use of a standard paper roll in case of need.
- Stainless steel AISI 304 one-piece seamless lid, 0,8 mm thick, bright finish, fully sealed. Fixed to the body by means of rivets that allows swinging down of the lid for the replenishment.
- Frontal window indicates refill time.

Technical Specifications

Dimensions	Ø 250 x 125 mm	1 layer paper roll capacity	250/300 m
Maximum dimensions	254 x 250 x 125 mm	2 layers paper roll capacity	180 m
Weight (empty)	1,3 Kg	Paper roll diameter	230 mm (maximum)
Recommended installation height	65-75 cm to bottom	Paper roll width	115 mm (maximum)
Installation height for disabled people	70 cm from the floor	Paper roll tube diameter	45 mm (minimum)

Operation

Pull visible toilet paper, at your own convenience.




Certificates & Qualifications

ISO 9001:2000.

Specification

Surface mounted toilet paper dispenser for industrial rolls of 250/300 m should be made of stainless steel AISI 304 one-piece body, 0,8 mm thick, round Ø 250 mm, fully sealed and with a catch system to prevent the opening of the door, bright finish. The supports of the screws in the back of the appliance should act as an anti-moisture support, as well as slots to avoid the screws damaging the toilet paper. It should be suitable to be mounted on the wall by means of 3 wood screws with their corresponding 5 mm wall plugs. It should include a lock system with standard mediclinics® key, that allows opening the lid for replenishment. The axis should be made of stainless steel AISI 304, 0,8 mm thick, for standard 45 mm paper roll tube, with inertial anti-spin retainer. The axis should allow the use of a standard paper roll in case of need. The lid should be made of stainless steel AISI 304 one-piece seamless, 0,8 mm thick, bright finish, fully sealed and fixed to the body by means of rivets that allows swinging down of the lid for the replenishment. The dispenser should have a frontal window which indicates refill time. Overall dimensions shall be Ø 250 x 125 mm.

Toilet paper dispenser for industrial rolls of 250/300 m shall be model PR0783C, stainless steel bright finish, manufactured by Mediclinics S.A., C/ Industria 54, E-08025 Barcelona, Spain.



Dim ± 4%

Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without warning or notice.

Revision 4-2004

© mediclinics S.A.

