

## Wash trough P3

Art. no. P3-FLEX

**GTIN** 8719585005349

**Art. no.** P3-600

**GTIN** 8719585005028

**Art. no.** P3-1200

**GTIN** 8719585005035

**Art. no.** P3-1500

**GTIN** 8719585005042

**Art. no.** P3-1800

**GTIN** 8719585005059

**Art. no.** P3-2100

**GTIN** 8719585005066

**Art. no.** P3-2400

**GTIN** 8719585005073

**Art. no.** P3-2800

**GTIN** 8719585005080

**Art. no.** P3-3000

**GTIN** 8719585005097

Overall dimension in mm 600-7 Outlet dimension in mm 1 ½"

**Material** 


Material thickness in mm Installation height in mm

600-3000 x 474 x 436

Stainless steel 18/10, AISI304, 1.4301

1 / 1,5

500/800/900





## **Description**

Flexible wash trough supplied with integrated wall brackets.

Inner corners with more than 90° angle, and pressed drain without screws and gasket ensure optimum hygiene and easy cleaning. The sink has a fall against the drain in the center. Soft transitions at all external angles counteract damage in the event of a fall against the trough. Safe and comfortable handle support at the bottom of the edges to prevent injury during assembly. The bowl has enough depth to accommodate a bucket.

Meets all requirements in EN 14296.

Washtroughs available in standard lengths 600, 1200, 1500, 1800, 2100, 2400, 2800 and 3000 mm. Washtroughs also available in any customer specified length between 600 and 3000. Art. Nr: P3-Flex

