



LOKI Warm-Air Hand Dryer

4000/4002/4004/4006



reddot winner 2021




High-speed
IR-sensor and electronic timer
5-year warranty

DAN DRYER LOKI high-speed hand dryer; award winning and ADA compliant. Its elegant and functional design is characterised by clean lines and rectangular shapes, which complements the surrounding architecture. The robust front plate with the high light guide maintains the design theme throughout the LOKI range.

Application

DAN DRYER LOKI is a compact, high-speed hand dryer in sleek design. Featuring short drying time and low maintenance, this reliable machine is suitable for all high traffic public and commercial areas.

Technical data

Type	LOKI Prod. No.: 4000, 4002, 4004, 4006 Warm-air hand dryer with IR sensor
Dimensions	H 300 x W 173 X D 102 mm
Material	Brushed or powder coated stainless steel
Drying cycle	10-15 sec.
Connection	230 V, 50/60 Hz, Class I 
Total wattage	1000 W
Noise level	69-76.6 dB @ 1 m
Max. air capacity	95-115 m/sec.
Net weight	5.0 kg
IP rating	IP24

Tender text

Touch-free hand dryer in stainless steel, brushed or powder coated Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP24, 230 V, 50/60 Hz, 840-1000 W, Class I (earthed), 69-76.6 dB @ 1 m dBA.
 Net weight: 5.0 kg. H: 300mm, W: 173mm, D: 102mm.

Compliance:

CE, WEEE, RoHS, UKCA

References

Offices and administration, shopping centres, restaurants, hotels and leisure, airports, schools, and sports facilities.

Standard colours

Prod. No. 4000: Brushed stainless steel
 Prod. No. 4002: RAL 9003, white, gloss 60
 Prod. No. 4004: RAL 9005, matt black, gloss 10
 Prod. No. 4006: RAL Classic colours

Activation

Infrared sensor and electronic timer. Touch free. Activation distance adjustable 172 mm (\pm 20 mm). Automatic stop after 60 seconds of continuous use.

Motor type

Commutator motor with carbon brushes.
 16,000-29,000 revolutions/min.

Protection

Automatic thermal cut-out in both motor and heating element.

Installation

Machine intended for wall-mounting and fixed installation via circuit-breaker. Installation must be carried out by a qualified electrician.