

TEMPOMATIC 4 electronic tap

Ref. 443400

Recessed mains supply



DESCRIPTION

TEMPOMATIC 4 electronic tap - Ref. 443400

Wall-mounted electronic basin tap:
 230/6V recessed mains supply.
 Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
 Scale-resistant flow straightener.
 Duty flush (~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated stainless steel body L. 130mm.
 Cap fixed in place by 2 concealed screws.
 Stopcock.
 Wall-mounted fixings.
 Recessed inlet.
 Anti-blocking security.
 Suitable for people with reduced mobility.
 10-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 electronic tap - Ref. 443400

Supply	230/6V mains supply (recessed)
Connector	M1/2"
Technology	Electronic
Spout length	130mm
Flow rate	3lpm
Norms	ACS CE
Warranty	10

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Recessed mains supply



Anti-bacterial duty flush

